



# i3CAMERA PRO P1201





## **Endless** compatibility


The plug & play connectivity allows endless compatibility with Microsoft Skype, Skype for Business, Teams, Zoom, Google Hangouts, Cisco Webex, Bleujeans, GoToMeeting, GoToWebinar and other video conferencing and recording applications that support USB cameras.

### Never miss a thing

The i3CAMERA Pro 4K camera has a Wide Dynamic Range lens making it optimal for close-quarter meetings or hybrid classrooms. With the face recognition, built-in noise reduction and low light capacity, meetings and lessons are a breeze.

With a built-in 12 meter omnidirectional microphone, sound won't be an issue in larger meeting rooms and classrooms, brining exceptional clarity and making sure you can always get your point across.





#### Omnidirectional mic

With a built in microphone array, using an omnidirectional pickup working up to 12 meters, nobody will be out of reach again. Thanks to the noise suppressing algorithm voices will be crisp and clear.

#### Low light support

With the CMOS image sensor the camera is able to give you clean and clear images, even under low light conditions.





#### Wide dynamic range

With a wide angle up to 120°, you'll get everyone on the picture. A the same time, it supports EPTZ to remotely control the Pan, Tilt, and Zoom of the camera.

#### Face recognition

By enabling the face recognition, the camera will center on the faces in the room, to avoid distraction of other element.



#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Model name	i3CAMERA PRO P1201
Article number	10010149
CAMERA	
Sensor	1/2.5", CMOS, Effective Pixel: 8.29M
Scanning mode	Progressive
Lens mount	M12
Lens	Focus: f=2.8mm, FOV: 120°
Minimal Illumination	0.05 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Manual
Camera Bracket	Optional Accessory
Digital Noise Reduction	2D, 3D digital noise reduction
Backlight compensation	Supported
Mounting	Supported: Display-Top-Edge Clip, Table-Top Stand, Tripod Mount Screw
	Optional Accessory: VESA mounting bracket.
USB-FEATURES	
Operating system	Windows® 7, Windows 8.1, Windows 10 or higher, macOS™ 10.10 or higher, Google™ Chromebook™ Version 29.0.1547.70 or higher, Linux
	2.4 GHz Intel® Core 2 Duo processor or higher2 GB RAM or moreUSB 2.0 port
Color system/Compression	H.264 / MJPEG / YUY2 / NV12
Video format	UHD@30fps, 1080p@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps
USB Video Communication Protocol	UVC 1.1
INPUT/OUTPUT INTERFACE	
USB interface	1x UXB 3.0: Type B
GENERAL SPECIFICATION	
Input voltage	5V (USB power supply)
Power consumption	600mA (max)
Compatibility	Plug and play USB connectivity, Suitable for Skype for Business, Teams, Zoom® Meetings, Cisco Webex, Hangouts & other.
Warranty	2 years