MAXHUB 01

# Commercial Display

Model Name: ND75CMA-T

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.





## Professional 4K Display

4K Resolution, 800 nits brightness Anti-Glare, 25% Haze



## Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



#### **External Control**

Display control through IP or RS232 protocol




### **Device Management**

Manage through cloud based MAXHUB Pivot



## **Built-in Speakers**

2 × 10W Dual speakers



# Upgrade Your Display

OPS slot availability to transform your display into a windows-based display



# 24/7 Operation

Reliable and continuous display performance



# **Energy Saving**

ErP Certified
Energy Star 8.0 Certified

Processor

Graphic

Memory

Storage

**OPS Slot** 

Operating System

**UI** Resolution

Display	
Screen Size (class)	75"
Diagonal	74.5" 189.3cm
Panel Type	VA
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	800 nits
Backlight Type	DLED
Contrast Ratio	6000:1 (Typ)
	1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	6.5ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	24 / 7
Orientation	Portrait / Landscape
Internal Player	

A55 × 4

4G

32G

4K

Mali-G52 × 2

Android 11.0

Connectivity	
Input	HDMI IN 2.0 × 3  USB Type-C × 1 (PD 65W)  USB Type-A 3.0 × 1 (for external peripherals)  USB Type-A 2.0 × 1 (only for firmware upgrade)  RJ45 IN × 1
Output	HDMI OUT 2.0 × 1  SPDIF × 1 (Optical)  RJ45 OUT × 1  AUDIO OUT × 1 (3.5mini jack)
External Control	RS232 × 1 / IR Receiver
Wi-Fi	Removable Wi-Fi Module Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax

Mechanical Specification				
Bezel Width (L × R × T × B)	15.9 / 15.9 / 15.9 / 15.9 mm 0.63 / 0.63 / 0.63 / 0.63 inch			
Product Dimension (W × H × D)	1685.6 × 963.7 × 81.6 mm 66.36 × 37.94 × 3.21 inch			
Package Dimension (W × H × D)	1863 × 1090 × 225 mm 73.35 × 42.91 × 8.86 inch			
Product Weight (Net)	34.65 kg / 76.40 pounds			
Package Weight (Gross)	48.15 kg / 106.15 pounds			
VESA Mount (mm)	800 × 600			
Handle	Yes			

Yes , 80pin

Environmental Conditions	
Operation Temperature	0°C~40°C
Operation Humidity	10%~90%RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~90%RH
Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Typical)	235W
Power Consumption (Max)	425W
Sound	
Speaker Power Output	2 × 10W
Certification	
Safety	IEC 62368-1
EMC	Class B
ErP	Yes
Energy Star	Yes
Features	
Built-In Media Player	Yes
Device Management System	MAXHUB Pivot
Screen Share	MAXHUB Share
Accessory	
Included in the package	Power Cord × 1

Included in th	e package		Power Cord × 1	
			HDMI Cable × 1	
			Wi-Fi Module × 1	
			Remote Control × 1	
			Wall Mount × 1	
Optional		S. C.		
	OPS (OPS62A)	Wireless Dongle (WT13)	Mobile Stand (ST41B)	Mobile Stand (ST23C)

# Warranty

Display 3 years warranty







