
EB-720



DATASHEET / BROCHURE



Compact, affordable display that creates a cost-effective and collaborative digital workspace in every environment.

Whatever the size of workspace, unrestricted and immersive presentations are now possible with this compact, affordable display solution. Due to a large display size, and flexible formats, content can be viewed from every angle, and participants can share directly from their own devices, for the perfect collaborative experience.

With the EB-720, users are no longer restricted to a single display size, with bright, large scalable options up to 110". Unlike flat-panel equivalents, there are no shadows, glare or blind spots, and the 3,800lm high-brightness laser light source can work when ambient lighting is also high. Multi-screen capability makes collaboration easy and intuitive, while a split-screen feature can show up to four inputs on one large display.

The viewing experience is more immersive, with multiple connectivity options enhancing exceptional image and sound quality. For the ultimate in engagement, wireless connectivity, including Screen Mirroring via Miracast, allows everyone to share content from their tablets, mobiles or laptops. By connecting an optional Epson document camera you can easily display images of 3D objects with incredible detail for the whole room to see.

Unlike flat panels displays, the EB-720 provides multiple display sizes and formats for one fixed cost. It also offers flexible mounting options to deploy a more comfortable view for delegates. When used with antibacterial whiteboards it provides more hygienic workspaces and is free from finger marks.

Sustainability is another strength, based on sustainable manufacturing, product usage and lifecycle.

KEY FEATURES

Any room, any size

- Bright, large-format display options up to 110"
- Every-angle viewing No restricted angles, shadows, glare or blind spots
- Multiple collaboration options Expand connectivity through BYOD devices, VC cameras and more
- Document camera compatibility Create a totally immersive experience with sound and visuals
- Exceptional reliability Maintenance-free laser technology for fitand-forget peace of mind





PRODUCT SPECIFICATIONS

| IMAGE Color Light Output 3.800 Lumen - 2.660 Lumen (economy) in accordance with ISO 21118:2013 White Light Output 3.800 Lumen - 2.660 Lumen (economy) in accordance with ISO 21118:2013 Resolution XGA, 1024 x 768, 4:3 Contrast Ratio 2.500.000: 1 Keystone Correction Manual vertical: ± 3 °, Manual horizontal ± 3 ° Colour Reproduction Upto 1.07 billion colours OPTICAL Throw Ratio Throw Ratio 0,32 - 0,43:1 Zoom Digital, Factor: 1 - 1,35 Screen Size 65 inches - 110 inches Projection Lens F Number 1,6 Projection Lens Focal Length 3,7 mm Projection Lens Focaus Manual Offset 7 : 1 CONNECTIVITY Interfaces Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Miracast, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input Epson iProjection App Ad-Hoc / Infrastructure ADVANCED FEATURES Security Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN security, Password protection | WHAT'S IN THE BOX Power cable Remote control incl. batteries Removable battery x2 Quick Start Guide OPTIONAL ACCESSORIES Table Mount for Ultra-short-throw Series V12H516040 Active Speakers (2 x 15W) - ELPSP02 V12H467040 Dual Function Wireless Adapter (5Ghz Miracast) - ELPAP11 V12H005A01 Optical Connection Base, ELPAP11 |
|---|--|
| LCD Panel 0,55 inch with C2 Fine IMAGE Color Light Output 3.800 Lumen - 2.660 Lumen (economy) in accordance with ISO 21118:2013 White Light Output 3.800 Lumen - 2.660 Lumen (economy) in accordance with ISO 21118:2013 Resolution XGA, 1024 × 766, 4:3 Contrast Ratio 2.500.000:1 Keystone Correction Manual vertical: ± 3 °, Manual horizontal ± 3 ° Colour Reproduction Upto 1.07 billion colours OPTICAL Throw Ratio 0.32 · 0,43:1 Zoren Size 65 inches - 110 inches Projection Lens F Number 1,6 Projection Lens Focal Length 3,7 mm Projection Lens Focas Manual Offset 7 : 1 CONNECTIVITY Interfaces Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base TX/ 10-B | Remote control incl. batteries Removable battery x2 Quick Start Guide OPTIONAL ACCESSORIES Table Mount for Ultra-short-throw Series V12H516040 Active Speakers (2 x 15W) - ELPSP02 V12H467040 Dual Function Wireless Adapter (5Ghz Miracast) - ELPAP11 V12H005A01 |
| Color Light Output3.800 Lumen - 2.660 Lumen (economy) In accordance with ISO 21118:2013White Light Output3.800 Lumen - 2.660 Lumen (economy) In accordance with ISO 21118:2013ResolutionXGA, 1024 x 768, 4:3Contrast Ratio2.500.000 : 1Keystone CorrectionManual vertical: ± 3 °, Manual horizontal ± 3 °Colour ReproductionUpto 1.07 billion coloursOPTICALThrow Ratio0,32 - 0,43:1ZoomDigital, Factor: 1 - 1,35Screen Size65 inches - 110 inchesProjection Lens F Number1,6Projection Lens Focal Length3,7 mnProjection Lens FocalManualOffset7 : 1CONNECTIVITYInterfacesUSB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-BaseTX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Miracast, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone inputEpson iProjection AppAd-Hoc / InfrastructureADVANCED FFATURESSecuritySecurityKensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protectionOther featuresA/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD pre- setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification, Microphone input, Network administration, Network projection, OSD copy function, Quc | Remote control incl. batteries Removable battery x2 Quick Start Guide OPTIONAL ACCESSORIES Table Mount for Ultra-short-throw Series V12H516040 Active Speakers (2 x 15W) - ELPSP02 V12H467040 Dual Function Wireless Adapter (5Ghz Miracast) - ELPAP11 V12H005A01 |
| Colour Reproduction Upto 1.07 billion colours OPTICAL Throw Ratio 0,32 - 0,43:1 Zoom Digital, Factor: 1 - 1,35 Screen Size 65 inches - 110 inches Projection Lens F Number 1,6 Projection Lens Focal Length 3,7 mm Projection Lens Focus Manual Offset 7 : 1 CONNECTIVITY Interfaces Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-TX/ | Table Mount for Ultra-short-throw Serie V12H516040 Active Speakers (2 x 15W) - ELPSP02 V12H467040 Dual Function Wireless Adapter (5Ghz Miracast) - ELPAP11 V12H005A01 |
| OPTICAL Throw Ratio 0,32 - 0,43:1 Zoom Digital, Factor: 1 - 1,35 Screen Size 65 inches - 110 inches Projection Lens F Number 1,6 Projection Lens Focal Length 3,7 mm Projection Lens Focus Manual Offset 7 : 1 CONNECTIVITY Interfaces Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Miracast, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input Epson iProjection App Ad-Hoc / Infrastructure ADVANCED FEATURES Security Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Other features A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD presetting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, Wireless LAN capable | V12H516040 Active Speakers (2 x 15W) - ELPSP02 V12H467040 Dual Function Wireless Adapter (5Ghz Miracast) -ELPAP11 V12H005A01 |
| Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Miracast, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input Ad-Hoc / Infrastructure ADVANCED FEATURES Security Security Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Other features A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD presetting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, Wireless LAN capable | Control and Connection Box - ELPCB0 |
| ADVANCED FEATURES Security Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Other features A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD presetting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, Wireless LAN capable | V12H927040 • Ceiling Pipe (700mm) - ELPFP14 V12H003P14 • Ceiling Pipe (450mm) - ELPFP13 V12H003P13 |
| Security Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Other features A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD presetting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, Wireless LAN capable | Wall Mount - ELPMB62 - EB-7xx / EB- |
| compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD pre- setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, Quick Corner, Schedule Function, Split-Screen- Function, Super resolution, Web Control, Web Remote, Wireless LAN capable | V12HA06A06 • Ceiling Mount (White) - ELPMB23 |
| | V12H003B23 Safety Wire - ELPWR01 V12H003W01 |
| Interactivity No | |
| Video Color Modes Blackboard, Cinema, Dynamic, Presentation, sRGB | |
| GENERAL Power consumption 255 Watt, 197 Watt (economy), 0,5 Watt (standby) Product dimensions 356 x 395 x 133 mm (Width x Depth x Height) Product weight 5,7 kg | |
| OTHER Warranty 60 months Carry in or 12.000 h | |

LOGISTICS INFORMATION

| SKU | V11HA01040 |
|-------------------|---------------|
| EAN code | 8715946681870 |
| Country of Origin | China |



Epson Norge Salgskontor: 67 11 37 70 Support/Service: 815 35 180 Forhåndssalg: 815 35 210 www.epson.no

Fjordveien 3 1363 Høvik

Varemerker og registrerte varemerker eies av Seiko Epson Corporation eller deres respektive innehavere. Produktopplysningene kan endres uten varsel.

EB-720

S

- ries ELPMB29
- 2
- Wireless &
- 303
- 3-8xx

