EB-L530U



The EB-L530U fixed lens laser projector offers 5,200 lumens and is ideal for education, corporate, retail and visitor attractions.

As the market leader in 3LCD technology, Epson continues to improve its high brightness laser projectors with even smaller and more compact display solutions. The EB-L530U delivers even more effective, practical and creative display applications across a number of different industries.

Bright, cost-effective display solutions

Providing bolder, brighter, more engaging and impactful displays even in brightlylit environments, the EB-L530U offers impressive 5,200-lumen brightness and WUXGA Full HD resolution at an affordable price. This means that users can upgrade to laser performance and reliability, with reduced power consumption, without paying a premium. It also features: 4K input support, detail enhancement technology, edge blending and wide lens shift to fit challenging installation environments. The EB-L530U is capable of up to 500-inch displays, without any reduction in clarity or vivid detail.

Enhanced connectivity

This display solution offers many different ways to connect, show multiple sources simultaneously and present wirelessly. The EB-L530U comes equipped with futureproofed connectivity options including HDMI and HDBaseT with 4K signal support, 5GHz wireless with enterprise security, upgraded Miracast, built-in media player and support for Epson's ELPWP10 wireless presentation system.

Easy and flexible installation

This stylish and compact projector supports 360 degree installation without compromising the display quality and supports 16:6 ultra-widescreen, HDMI output and edge blending for multi-projector installs.

KEY FEATURES

- 5,200-lumen brightness
 Crisp images and bright colours, even in well-lit rooms
- WUXGA resolution Sharp Full HD images for excellent clarity
- Futureproofed connectivity options 4K input support, HDMI, HDBaseT, integrated Wi-Fi and screen mirroring
- Easy, flexible installation Lightweight and compact design with wide lens shift
- Support social distancing Scalable display size of up to 500 inches



EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY Projection System	3LCD Technology, RGB liquid crystal shutter	WHAT
LCD Panel	0.67 inch with C2 Fine	
		 Powe
IMAGE		 Remo
Color Light Output	5,200 Lumen- 3,640 Lumen (economy) In accordance with IDMS15.4	 Cable
White Light Output	5,200 Lumen - 3,640 Lumen (economy) In accordance with ISO 21118:2012	
Resolution	WUXGA, 1920 x 1200, 16:10	• User
High Definition	Full HD	 Warra
Aspect Ratio	16:10	 Main
Contrast Ratio	Over 2,500,000 : 1	
Light source	Laser	
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco	OPTIO
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 ° Upto 1.07 billion colours	
Colour Reproduction	Opto 1.07 billion colours	 Epson
OPTICAL		
Throw Ratio	1.35 - 2.20:1	 Epson
Zoom	Manual, Factor: 1 - 1.6	
Lens	Optical	 Air Filte
Lens Shift	Manual - Vertical ± 50 %, horizontal ± 20 %	
Screen Size	50 inches - 500 inches	 Ceiling
Projection Lens Focus	Manual	
Projection Distance Wide	1.4 m - 14.8 m	 Ceiling
Projection Distance Tele	2.4 m - 23.8 m	5
Projection Distance Wide/Te	ele 1.44 m - 23.84 m	 Ceiling
Projection Lens F Number	1.5 - 1.7	e oomig
CONNECTIVITY		 Ceiling
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T),	0
	Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN b/g/n (2.4GHz), Wireless LAN a/n (5GHz),	 Adapte
	VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Stereo mini jack audio out, Stereo mini	
	jack audio in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback	 Safety
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Video Color Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection	
Projector control	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4	
	Simple Device Discovery Protocol	
GENERAL		
Power consumption	293 Watt, 223 Watt (economy), 0.3 Watt (standby)	
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz	
Product dimensions	440 x 339 x 136 mm (Width x Depth x Height)	
Product weight	8.2 kg	
Noise Level Colour	Normal: 31 dB (A) - Economy: 23 dB (A) White	
	Winto	
OTHER		
Warranty	36 months Carry in	
	Optional warranty extension available	

EB-L530U

T'S IN THE BOX

- er cable
- ote control incl. batteries
- e cover
- guide
- ranty Documents
- unit

ONAL ACCESSORIES

- ELPWP10 Wireless Presentation System
- ELPWT01 Wireless Transmitter
- ter ELPAF56 L600/EB-14XX Series
- Mount (White) ELPMB22
- Mount (Low profile) ELPMB30
- Pipe (450mm) ELPFP13
- Pipe (700mm) ELPFP14
- ter ELPAP11 Wireless LAN (5GHz)
- Wire ELPWR01

