


Evolution XPC OFC LSOH Speaker Cable Black



Product overview

Part number	301-050, 301-051, 301-052, 301-053, 301-106, 301-107, 301-108, 301-109
Product description	Evolution XPC OFC LSOH Speaker Cable Black

Cable construction

Conductor	0.75 mm ² 24 x 0.2 mm
	1.0 mm ² 32 x 0.2 mm
	1.5 mm ² 30 x 0.25 mm
	2.5 mm ² 50 x 0.25 mm
	4.0 mm ² 56 x 0.30 mm
Insulation	Material: LSOH
	Insulation colour : 2 Core Red & Blue
	4 Core Red, Blue, Green, Yellow
	8 Core Red, Blue, Green, Yellow, Black, White, Purple & Brown

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Jacket

Material: LSOH

Colour : Black

Diameter : 0.75 mm² x 2 core : 6.2 mm
1.0 mm² x 2 core : 6.5 mm
1.5 mm² x 2 core : 7.3 mm
2.5 mm² x 2 core : 9 mm
2.5 mm² x 4 core : 10.6 mm
4.0 mm² x 2 core : 10 mm
4.0 mm² x 4 core : 12.2 mm
4.0 mm² x 8 core : 16 mm

Printing

Evolution XPC OFC 2 x 0.75 mm² Speaker Cable LSOH Black 301-050
Evolution XPC OFC 2 x 1.0 mm² Speaker Cable LSOH Black 301-051
Evolution XPC OFC 2 x 1.5 mm² Speaker Cable LSOH Black 301-052
Evolution XPC OFC 2 x 2.5 mm² Speaker Cable LSOH Black 301-053
Evolution XPC OFC 4 x 2.5 mm² Speaker Cable LSOH Black 301-106
Evolution XPC OFC 2 x 4.0 mm² Speaker Cable LSOH Black 301-107
Evolution XPC OFC 4 x 4.0 mm² Speaker Cable LSOH Black 301-108
Evolution XPC OFC 8 x 4.0 mm² Speaker Cable LSOH Black 301-109

Reel lengths

100 m / 200 m / 500 m

Electrical characteristics at 20°C

Conductor Resistance	0.75 mm ²	26.00 Ω/m @ 20°C
	1.0 mm ²	18.10 Ω/m @ 20°C
	1.5 mm ²	11.00 Ω/m @ 20°C
	2.5 mm ²	7.30 Ω/m @ 20°C
	4.0 mm ²	4.60 Ω/m @ 20°C

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.