

iTrans DU-TR-22C (V2)

Dante I/O Converter over USB C

Datasheet V1.0



1. INTRODUCTION

Thanks for choosing the **iTrans DU-TR-22C (V2)**. It connects to your Dante network and supports 2X2 channels of bidirectional audio, allowing PC and mobile device to playout and receive audio with your Dante devices using a USB-A/C connection.

2. FEATURES

- Plug and Play
- 24-bit audio support
- 2X2 audio channel
- Supports 802.3af PoE

3. PANEL DESCRIPTION



① **RJ45:** Dante network communication port. Green steady light indicates system ready; yellow flashing light indicates link/data traffic. The green light will flash to identify the device when clicking the Dante Controller “Identify” button (an eye-shaped symbol) on the host computer.

② **USB-C:** 1 x USB-C, compliant USB 2.0 device.

4. DATASHEET

Model	iTrans DU-TR-22C (v2)
Name	Dante I/O Converter over USB C
Power	802.3af PoE
Sample Rate	48 kHz
Bit Depth	24
Operation Temperature	-5 to +55°C
Storage Temperature	-25 to +70°C
Power Consumption	9W(Max)
Dimension (W*H*D)	114x 48 x 28 mm
Case	Metal
Color	Black
Cable length	20cm
Net Weight	70g